

TECHNICAL DATA SHEET



Since 2011

CLEAN AGENT FIRE EXTINGUISHER 4 KG

Description

We, **Palladium Safety Solutions Pvt. Ltd.** is a **Manufacturer** of Fire Extinguishers. A **fire extinguisher** is an active fire protection device used to extinguish or control small fires, often in emergency situations. Our Clean Agent Extinguisher is of Stored Pressure Type.

- **Class A Fire:** Wood, Textiles, Paper, Clothes, Cotton mill, Jute Mill etc.
- **Class B Fire:** Petroleum, Oil, Paint, Varnish, Solvent, Aviation Fuel, Flammable and Volatile Liquids etc.
- **Class C Fire:** Flammable Gases, Industrial Gases etc.
- As Well As **Electrical Fires**



Specification:

MODEL NO.	PSS-CAFE-4
Capacity	4 KG
Anti-Corrosive Inhibitor	Epoxy Polyester Powder Coating
Type of Extinguisher	Stored Pressure
Type of Extinguishing Media	Clean Agent Gas
Expellant	Pressurized With N2 gas
Minimum Effective Discharge	95%
Range of Discharge (Mtrs.)	< 2 mtr
Duration of Discharge (sec.)	< 13 Sec
Testing Pressure (kgf/cm ²)	35 kgf/cm ²
Charged Pressure (kgf/cm ²)	15 kgf/cm ²
Operating Temperature °(c)	(-) ¹⁰ ° C to (+) ⁶⁰ ° C
Operating Valve	Squeeze Grip Type with Discharge Hose and Nozzle

PALLADIUM SAFETY SOLUTIONS PVT. LTD.

An ISO 9001 : 2015 Certified Company

Email: customercare@palladiumss.com Web: www.palladiumss.com

DELHI I CHENNAI