

TECHNICAL DATA SHEET



ABC DRY CHEMICAL POWDER FIRE EXTINGUISHER 9KG

PalEx ABC Dry Powder (Stored Pressure) 9kg Fire Extinguishers applicable Class of fire - A, B, C and electrically started fires. Which involves flammable solids, liquids and gases.

Brief description: ABC Dry Powder MAP Fire Extinguishers with nominal charge of 9kg ($\pm 5\%$). Constructed of Stainless Steel 304 made up to 1.5mm. Approved Fire Ratings 4A, 144B with an effective throw of about 4.5meters and discharge about 95%.



1. GENERAL DATA :-

Manufacturer	Palladium Safety Solutions Pvt. Ltd.
Trade Mark/Brand	“PALEX”
BIS Standard Code	IS 15683:2018
Type	Portable Fire Extinguisher Stored Pressure Type

2. PERFORMANCE DATA :-

Capacity	9KG
Fire Rating	4A, 144 B (Class “A” – Solid Fuel. Class “B” – Liquid Fuel)
Performance requirements	Min. Effective discharge time : 13 Sec. (Actual : 21 Sec. Approx.) Min. Bulk range of discharge : 2 Mtr. (Actual : 4.5 Mtr. Approx.) Min. Percentage of discharge : 85% (Actual : 95% Approx.)
Working Temperature	(-) 10°C To (+) 60°C
Service Pressure	15 BAR
Hydraulic Test Pressure	35 BAR

3. MATERIAL OF CONSTRUCTION :-

Body	Stainless Steel (S.S) 304
Extinguishing Media	Mono Ammonium Phosphate (50% or 90%) confirming to IS 4308:2019
Neck Ring	Stain less Steel 304
Valve	Brass – Male Threaded, Squeeze Grip Type
Syphon Tube	PVC / Plastic
Hose Pipe	PVC Braided (550mm ± 10 mm)
Pressure Gauge	As per IS 15683:2018
Discharge Nozzle	PVC
Wall Mounting Bracket	Mild Steel (Powder Coated)
Discharge Tube Holder	Plastic/PVC

4. QUALITY TEST :-

Hydro Pressure Test (Pt)	35 bar (3.5 MPa) Hold for 1 min.
Min. Burst pressure (Pb) for body	55 bar (5.5 MPa) Hold for 1 min.
Leakage test	Inverted glass jar / Soap solution
Partial discharge	The second pressure or weight shall not be less than 75% of the first after interruption of the Discharge

5. DIMENSIONS :-

Diameter	180mm $\pm$ 10mm
Height	560mm $\pm$ 10mm
Thickness	Made up from 1.5mm Thick Sheet
Full/Gross Weight of Extinguisher	12.3KG $\pm$ 5% (Approx.)

6. Anti – Corrosion Treatment :-

Phosphate Treatment Followed by epoxy powder coating of body DFT not less than 50 micron.

7. MISCELLEANEOUS :-

Inspection & testing	As per approved QAP
Finish	PO Red as per IS : 5 (Shade 538)
Marking	As per IS 15683:2018
Approvals	BIS (BUREAU OF INDIAN STANDARD) & CE
Maintenance, care and refilling	As per IS 2190

8. PACKING :-

Box Type	Corrugated Boxes
Dimension	190mm X 190mm X 600mm

9. IN BOX ACCESSORIES:-

Wall Mounting Bracket	1 Nos
Fire Extinguisher	1 No (Fully Assembled)

PALLADIUM SAFETY SOLUTIONS PVT. LTD.

An ISO 9001 : 2015 Certified Company

Email: customercare@palladiumss.com Web: www.palladiumss.com

DELHI I GURUGRAM I CHENNAI